

SHED MASTER® GDO-8



COMMERCIAL ROLLER DOOR OPENER

An opener with versatility, no matter what the environment.

Automatic Technology's Shed Master® opener is the ideal solution for exposed areas, such as perimeter doors and open carports. With a tough, IP24 rated weather resistant housing and a slim fit design, the Shed Master® is suitable for even the tightest of spaces.

Just because it's rugged doesn't mean this roller door opener isn't fit for all circumstances. Standard features include Intelligent Safety Systems, Door Profiling and TrioCode™128 transmitter system ensuring optimum safety and security. The Shed Master® comes with a keyed lockout feature which prevents unauthorised manual operation of the door. If you need a solution to last in all weather conditions, look no further than Shed Master®.

WHAT'S INCLUDED:



Weather Resistant Opener



2x TrioCode™128 transmitters



Keyed Lockout

AT A GLANCE:

SECURE & RELIABLE TRANSMITTERS

The TrioCode™128 remote control ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol for the ultimate in security.



WEATHER-RESISTANT HOUSING

Designed for installation on uncovered or exposed doors, this opener has a weather resistant rating of IP24.

KEYED & ELECTRONIC LOCKOUT

As the Shed Master® can be installed in exposed locations, a keyed lockout is included to stop unwanted persons reaching over the fence and disengaging the door to manual mode. Also, the control panel can be similarly locked out to prevent unauthorised usage.

INTELLIGENCE

This opener is top of its range with built-in intelligent features such as Intelligent Safety System and Door Profiling – meaning the door adjusts itself when opening and closing or if blocked.

TECHNICAL SPECIFICATIONS



SHED MASTER® GDO-8

Power	Input Voltage	230-240V a.c. 1-phase
	Transformer Rating	72VA
	Standby Power	2.8W
	Motor Type	24V d.c. Permanent Magnet
	Motor Power	100W
	Peak Driving Force	600N
Door Sizes	Rated Door Area	15m ²
	Typical Travel Speed	100mm/sec
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	Code hopping (Non-linear encryption algorithm)
	Code Combinations	3.4x10 ³⁸ code combinations
	Transmitter Type	TrioCode™128
	Transmitter Capacity (x 4-button registers)	8
Additional Features	Courtesy Light	Optional
	Weather Resistance Rating	IP24
	Lockout System	Keyed lockout for manual release Electronic lockout for control panel buttons
	Safety Beam Compatibility	1 x 3-wire Safety Beam
Warranty*	2 year/5,000 cycles	

SAFETY & SECURITY FEATURES

- Intelligent Safety System
- Door Profiling
- TrioCode™128

POWER & MOUNTING SYSTEM

- DC Motor – 1000N
- Slim Fit

OPERATING MODES

- Weather Resistant
- Service Indicator
- Lockout System

OPTIONS



LIGHT & CONTROL MODULE

Weatherproof, secure access without a transmitter or keys is great for school kids and active families.



WIRELESS KEYPAD

This weather-resistant hard wired module contains a push button to operate your door, and LEDs to illuminate the area.



SMARTSOLAR™ READY

Using only one solar panel the sun does all the work for you.

For more product information, visit www.automatictechnology.com/au

©2024 Automatic Technology (Australia) Pty Ltd. All rights reserved. The Automatic Technology logos, feature icons, Shed Master® & TrioCode™ are registered trademarks. In an ongoing commitment to product quality, the specifications may change from time to time – E&OE Automatic Technology (Australia) Pty Ltd, 6-8 Fiveways Boulevard, Keysborough VIC 3173, www.automatictechnology.com/au, 1300 133 944. *Please see full warranty terms and conditions at www.automatictechnology.com/au. This brochure is not evidence of our warranty. Our warranty is in addition to any consumer guarantees that may apply under the Australian Consumer Law. Date: November 2024

automatic
TECHNOLOGY®